

Journal of Materials Science Research and Reviews

Volume 7, Issue 4, Page 507-520, 2024; Article no.JMSRR.122377

Assessment of Groundwater Quality and Contamination Levels Near Dumpsites and Slaughterhouses in Cross River State, Nigeria

Ekpe Glory Essien a* , Unoh Florence Ben ^b , Etim Daniel Offiong ^c and Bebia Obase Etta ^a

^aDepartment of Genetics and Biotechnology, University of Calabar, Calabar, Cross River State, Nigeria. ^bDepartment of Science Laboratory Technology, University of Calabar, Calabar, Cross River State,

Nigeria.

^cDepartment of Botany, University of Calabar, Calabar, Cross River State, Nigeria.

Authors' contributions

This work was carried out in collaboration among all authors. Author EGE designed the study and wrote the protocol. Author UFB wrote the first draft of the manuscript. Author EDO managed the analyses of the study. While author BOE managed the literature searches. All authors read and approved the final manuscript.

Article Information

Open Peer Review History:

This journal follows the Advanced Open Peer Review policy. Identity of the Reviewers, Editor(s) and additional Reviewers, peer review comments, different versions of the manuscript, comments of the editors, etc are available here: <https://www.sdiarticle5.com/review-history/122377>

Original Research Article

Received: 19/06/2024 Accepted: 21/08/2024 Published: 01/09/2024

ABSTRACT

Aims: To assess the level of total dissolved solids (TDS) and heavy metals contamination of groundwater, biochemical oxygen demand (BOD), and quality of groundwater from boreholes close to dumpsites and slaughterhouse in six L.G.A in Cross River State.

**Corresponding author: Email: princessge2005@yahoo.com;*

Cite as: Essien, Ekpe Glory, Unoh Florence Ben, Etim Daniel Offiong, and Bebia Obase Etta. 2024. "Assessment of Groundwater Quality and Contamination Levels Near Dumpsites and Slaughterhouses in Cross River State, Nigeria". Journal of Materials Science Research and Reviews 7 (4):507-20. https://journaljmsrr.com/index.php/JMSRR/article/view/346.

Study Design: The study was a Completely Randomized Design (CRD), 3x6 factorial experimental design.

Place and Duration of Study: Cross River State Water Board Laboratory for analysis, between September and October 2023 (8 weeks).

Methodology: Standard laboratory procedures were carried out to determine, total dissolved solids (TDS), 10 ml of each heavy metal (nitrate, chloride, copper, zinc, aluminium, Fluoride, and ammonia) sample from each of six locations, was measured into a square sample cell for heavy metal determination. Physical analysis of water samples for temperature, pH, conductivity, and BOD, were determined using thermometer, pH meter, Conductivity meter, BOD meter, respectively. **Results:** The results revealed that the pH for the ground water samples ranged from 4.26 – 7.0 indicating acidity in some of the water samples. The value for conductivity ranged between 31.33 – 603.67 µs/cm and was above the WHO standard for drinking water, fluoride ranged between 0.10 – 0.68mg/L and calcium with a range of 11.13 – 2.1.17mg/L which was within the WHO and NIS permissible limits. Standard BOD values were higher than all the controls. Findings suggest serious health implications. Gastrointestinal issues, irritation to the skin and eyes, hypertension, kidney damage, and complications for individuals with existing cardiovascular conditions are possible dangers. Again, higher BOD values suggest the presence of organic pollutants and microorganisms that deplete oxygen levels, making the water potentially harmful for drinking and aquatic life. **Conclusion:** Evidence from Increased acidity, conductivity, and BOD values, suggest there is high

level of contamination of groundwater sources within the study area. This calls for urgent policy and health interventions.

Keywords: Physiochemical; contamination; groundwater; dumpsites; pollution-prone; heavy metals.

1. INTRODUCTION

Cross River State, known for its diverse ecosystems and significant water resources, faces increasing challenges due to urbanization, industrial activities, and agricultural practices that contribute to water pollution. The knowledge of areas where pollution levels exceed safe limits is invaluable and necessary information for requisite actions aimed at reducing incidence of contaminating water bodies. This study aimed at investigating the quality of surface and groundwater resources for possible pollution, by determining the physicochemical properties, and the heavy metal content of samples, in pollutionprone areas in Cross River State, Nigeria.

Groundwater contamination by heavy metals presents a significant threat to both public health and environmental integrity. Studies [1,2,3] have examined the impact of heavy metal contamination of groundwater. A broad review of latest advancements in water quality assessment, highlighting the increasing prevalence of heavy metal contamination in groundwater was carried out by Kumar [1]. The authors emphasize that even low concentrations of heavy metals, including arsenic, lead, and mercury, can pose significant health risks, contributing to chronic diseases such as cancer and neurological disorders. Concerning the sources of heavy metal contamination in

groundwater, Zhang [2], identified industrial discharge, agricultural runoff, and mining activities as primary contributors. The study details the severe health implications of exposure to heavy metals like cadmium, chromium, and lead, which include developmental problems in children, respiratory issues, and organ damage. A recent research by Ogunfowokan [3] explored the relationship between urbanization and groundwater quality, particularly in the context of heavy metal contamination. Their case study reveals that urbanization, characterized by increased industrial activities, waste generation, and infrastructure development, significantly exacerbates the risk of heavy metal contamination in groundwater. The study found elevated levels of metals such as zinc, lead, and copper in groundwater samples from urban areas compared to rural regions.

1.1 Physicochemical Properties

The physicochemical properties of water, including pH, electrical conductivity (EC), total dissolved solids (TDS), turbidity, dissolved oxygen (DO), and chemical oxygen demand (COD), are essential parameters for evaluating water quality. These properties are influenced by both natural factors (such as geological formations) and anthropogenic activities (such as industrial discharges and agricultural runoff). The pH of water as a critical parameter, affects the solubility and toxicity of heavy metals and other pollutants. Water with a pH outside the neutral range (6.5-8.5) can indicate contamination from acidic or alkaline pollutants. For instance, studies in industrial areas have reported deviations from the neutral pH range due to the discharge of acidic industrial effluents [4].

1.2 Electrical Conductivity (EC) and Total Dissolved Solids (TDS)

The study by Rakib [5] focuses on the salinization of groundwater and its implications for drinking water quality in the southwestern coast of Bangladesh. The study provides significant insights into the role of Electrical Conductivity (EC) and Total Dissolved Solids (TDS) as key indicators of groundwater salinization and pollution. EC was used in the study to assess the extent of groundwater salinization. The elevated EC levels in the groundwater samples from the region are indicative of high salinity, primarily due to the intrusion of seawater into the aquifers. Authors Rakib [5] highlights that EC measurements provide a quick and reliable assessment of the ionic content of groundwater, which directly relates to the presence of dissolved salts and minerals. Elevated EC values in the study area suggested that the groundwater is not only saline but also potentially contaminated with other dissolved substances, posing a risk to drinking water quality. Gapparov [6] emphasized the importance of EC and TDS as critical parameters for assessing the salinity and overall quality of water resources, arguing that the characteristics of water resources in Uzbekistan are analyzed through the measurement EC as an indicator of water quality.

Turbidity: Turbidity refers to the cloudiness or haziness of a fluid caused by large numbers of individual particles that are generally invisible to the naked eye, similar to smoke in the air. It is an important indicator of water quality, particularly in effluents, as it can affect the penetration of light into the water, which in turn affects aquatic life. Chris-Otubor [7], evaluated turbidity as one of the key parameters in assessing the quality of industrial effluents discharged into the environment in Jos metropolis, Plateau State, Nigeria. The study found that the turbidity levels in the sampled industrial effluents varied significantly across different industries. High turbidity values were noted in effluents from certain industries, indicating the presence of suspended particles and possibly contaminants that contribute to the water's cloudiness. These

high turbidity levels could have adverse effects on receiving water bodies by reducing the clarity of the water, which can hinder photosynthesis in aquatic plants and disrupt the habitat of aquatic organisms.

Similarly, a recent research Sanad [8] found that turbidity levels varied across different sampling sites in the Mnasra region. Elevated turbidity values in certain areas indicated potential contamination, which could be attributed to agricultural runoff, improper waste disposal, or infiltration of surface water into the groundwater system. The researchers noted that high turbidity levels could impair the aesthetic and portability of groundwater, as well as interfere with water treatment processes. Authors believe the presence of high turbidity in groundwater is a concern for both environmental and public health. It can harbor pathogens, reduce the effectiveness of disinfection processes, and make the water less suitable for consumption and irrigation.

Dissolved Oxygen (DO) and Chemical Oxygen Demand (COD): the level of environmental water pollution can be seen by knowing the dissolved oxygen content in the water. Dissolved oxygen is a basic requirement for plant and animal life in water. Water is categorized as polluted water if the dissolved oxygen concentration falls below the limit required for biota [9]. The main cause of reduced dissolved oxygen in water is the presence of waste materials that consume oxygen. These materials consist of materials that are easily decomposed by bacteria in the presence of oxygen. The oxygen available in water is consumed by bacteria that actively break down these materials [10].

DO represents the amount of oxygen that is present in a body of water, which is necessary for the survival of aquatic life [11,7]. It is among the crucial parameters used in assessing the quality of water bodies and wastewater. Aniyikaiye [11] found that the wastewater discharge from selected paint industries in Lagos, Nigeria, exhibited low levels of DO. This indicates that the oxygen available in the wastewater is insufficient to support aquatic life. which can lead to hypoxic conditions. Such low DO levels are often a result of the decomposition of organic matter, which consumes oxygen in the process.

COD measures the total quantity of oxygen required to oxidize both organic and inorganic compounds in water. It is an indicator of the amount of pollution in the water, specifically from organic pollutants. The COD values in the wastewater from the paint industries were found to be high, suggesting a significant presence of organic pollutants. High COD levels indicate that a large amount of oxygen would be needed to break down the organic material present in the wastewater. This high organic load can lead to oxygen depletion in receiving water bodies, adversely affecting water quality and aquatic life [11].

Heavy metals are a class of inherently dense and toxic elements, which have become pervasive contaminants of serious concern within the environmental landscape worldwide [12]. A study [13] focused on assessing the quality of groundwater in Karu, Central Nigeria revealed that the concentrations of heavy metals such as cadmium (Cd), chromium (Cr), copper (Cu), iron (Fe), manganese (Mn), nickel (Ni), lead (Pb), and zinc (Zn) in the groundwater samples were generally within the permissible limits set by the World Health Organization (WHO). However, certain locations exhibited elevated levels of lead and nickel, which pose significant health risks due to their toxicity and potential to cause longterm health effects such as kidney damage and neurological disorders.

In another instance, Mawari [14]**,** investigated the human health risks associated with heavy metal contamination in ground and surface water, in Maharashtra, India. The study found that the concentrations of heavy metals like arsenic (As), cadmium (Cd), lead (Pb), and mercury (Hg) in some water samples exceeded the WHO guidelines, indicating potential health risks, including cancer, neurological damage, and developmental issues in children.

In consideration of the broader impact of heavy metal contamination in water on living organisms, Singh [15] correlated the non-biodegradable nature of heavy metals with the propensity of their accumulation in aquatic ecosystems, leading to bioaccumulation in organisms. This bioaccumulation can cause a range of toxic effects, including carcinogenicity, neurotoxicity, and damage to vital organs such as the liver and kidneys in humans and animals.

2. MATERIALS AND METHODS

2.1 Study Area

Groundwater samples for the study were collected from diverse sources within six Local Government Areas (LGA) in Cross River State. These locations varied, including rural villages, urban centers, and border areas. The sampling sites including dumpsites and slaughterhouse were located at various village settlements within Yakurr (Latitude 5°45'34" N to 5°48.682' N, Longitude: 8°5'18" E to 8°5'23" E), and Ikom LGA (Latitude 5.9667° N to 6.2000° N, Longitude 8.6000° E to 8.8000° E), situated in the Central Senatorial District, featured village settlements and diverse occupations, including farming and civil service. Despite potential concerns about water quality, the residents of these areas relied heavily on groundwater sources for everyday use.

The Southern Senatorial District, home to Akamkpa (Latitude 5.2500° N to 5.4500° N, Longitude: 8.2500° E to 8.4500° E) and Calabar Municipality (Calabar Municipality: Latitude 4.9200° N to 4.9900° N, Longitude 8.3000° E to 8.3800° E), presented an interesting contrast with its urban features and surrounding rural areas. Yala and Ogoja are located in the Northern Senatorial District of the State. Ogoja lies between Latitude 6.5500° N to 6.7500° N, and Longitude: 8.6500° E to 8.8500° E, while Yala lies between Latitude 6.5000° N to 7.0000° N, and Longitude: 8.5000° E to 9.0000° E.

2.2 Ground Water Sample Collection from Boreholes

Groundwater samples for physicochemical and heavy metal analysis were collected from boreholes across six Local Government Areas (Akamkpa, Calabar Municipality, Ikom, Ogoja, Yakurr, and Yala) in the state. In total, 54 water samples were gathered and immediately placed in sterile, acidified bottles to preclude contamination. The bottles were covered, placed in an ice pack, and conveyed to the Cross River State Water Board Laboratory for analysis. During sample collection, the mouth of the tap was sterilized using methylated spirit and the water was allowed to flow for two minutes at maximum flow before being collected in the bottles.

2.3 Experimental Design

The study was a Completely Randomized Design (CRD), 3x6 factorial experimental design.

Factor 1: Sources (Control, Dumpsite and Abattoir).

Factor 2: Six Local government Area (Akamkpa, Calabar Municipality, Ikom, Ogoja, Yakurr, and Yala).

2.4 Physical Analysis of Water Samples

Temperature: This was determined with the thermometer. The thermometer was inserted into the water sample in a beaker and the reading was noted [16,17].

pH: The pH was determined with a pH meter (Model Hach Sension +). The pH meter probe was inserted into the water sample in a beaker, the read key was pressed and the pH reading was taken [16,17].

Conductivity: Conductivity meter (Model: Orion 3 Star) was used. The conductivity meter probe was rinsed with distilled water and inserted into the sample in a beaker, the conductivity reading was displayed [16,17].

BOD: BOD meter (Model: HACH HQ40D) was used to determine this parameter. The meter probe was rinsed with distilled water and inserted into the sample. BOD reading was displayed on activation of the read key [16,17].

2.5 Chemical Analysis of Water Sample

Total iron: The multi-cell adapter with the I-inch square cell holder was inserted into the electronic device after the "total iron" test was selected from a button on the electronic device. Then a clean square sample cell was filled with 10ml of the sample. Contents of one ferrover iron reagent powder pillow was added to the sample cell and swirled to mix. An orange colour was formed indicating the presence of iron [16,18].

Manganese: The multi-cell adapter with I-inch square cell holder was inserted in the electronic device after the "manganese" test was selected from a button. Then a square sample cell was filled with 10ml of the sample. Contents of one buffer powder pillow, citrate type of manganese stopper was added. Then contents of one sodium periodate powder pillow was added to the sample cell stopper and inverted to mix. A violet colour indicated the presence of manganese [16,18].

Copper: A square sample cell was filled with 10 ml of the sample. The blank was inserted into the cell holder with the fill line facing the user. Zero was pressed on the timer with the display showing 0.00 mg/l Cu. Within 30 minutes after the timer expired, prepared samples were inserted into the cell holder with the fill line facing the user. Then results were taken in mg/l Cu [16,18].

Nitrate: The "nitrate" test was selected from a button on the electronic device, and then the multi cell adapter with I-inch square cell holder was inserted facing the user. The square sample cell was filled with 10 ml of the sample. Contents of one Nitra Ver 5 nitrate reagent powder pillow were added. Then OK was pressed on the timer. A one-minute reaction period began, and then the cell was shaken vigorously until the time expired. The timer "OK" was pressed again. Then a five-minute reaction period began. An amber colour developed showing the presence of nitrate [16].

Phosphorus: A square sample cell was filled with 10 ml of the sample. The blank was inserted into the cell holder. The ZERO was pressed on the button, with the display showing 0.00 mg/l PO⁴ 3- . The prepared sample was wiped and inserted into the cell holder with the fill line facing the user. Then results were taken in mg/l $PO₄3$ [16,17].

Ammonia: The "ammonia" test was selected from a button on the electronic device and the multi cell adapter with one-inch square holder was inserted. The square sample cell was filled with 10ml of the sample. Contents of one ammonia salicyclate powder pillow were added to each cell stopper and then shake to dissolve. Then the OK button was pressed, a 15-minute reaction period began. A green color developed showing the presence of ammonia-nitrogen. When the timer expired, the blank was inserted into the cell holder with the fill line facing the user. Zero was pressed on the timer with the display showing 0.00 mg/l NH3-N. The sample was wiped and inserted into the cell holder and results were taken in mg/l $NH₃[16]$.

Zinc: Ten mililitres of the sample solution was poured into a square sample cell. With the use of a plastic dropper, 0.5 ml of cyclohexanone was added to the solution in the graduated cylinder. Then OK was pressed on the timer. A 30 second reaction period began, during the period the prepared sample in the cylinder was shaken vigorously. A colour change was observed, which depending on the zinc concentration could be reddish orange, brown or blue [16,18].

Chromium: Multi-cell Adapter was inserted with the 1-inch square cell holder facing the user and the required test selected. A square sample cell was filled with 10ml of sample. The contents of one ChromaVer® 3 Reagent Powder Pillow was added to the sample cell and swirled to mix. TIMER>OK button was pressed for a five-minute reaction period will begin. A purple color was formed to indicate the presence of hexavalent chromium. When the timer expired, a second square sample cell was filled with 10ml of sample, the blank was inserted into the cell holder with the fill line facing the user. ZERO button was pressed, the display showed 0.000 mg/L Cr6+

2.6 Statistical Analysis

The collected data were subjected to a two-way Analysis of Variance (ANOVA) while significant means were separated using Least Significant Difference (LSD) test at 5% and 1% probability level.

3. RESULTS

3.1 Physicochemical Properties of Ground Water

pH: The result as presented on Table 1 show that the borehole located in the non-pollution prone area in Yala LGA had the highest pH value and significantly higher (P<0.05) than the value obtained from other sources. This was followed by the pH obtained from Akamkpa (control, dumpsite), Calabar Municipality (control), Ikom (control, dumpsite), Ogoja (control, dumpsites, slaughterhouse), Yala (dumpsite, slaughterhouse) with no significant difference (P>0.05) in mean, the pH values obtained from these areas appears to be slightly acidic, which further reduces in areas like Akamkpa and Ikom (slaughterhouse), Yakurr (control, dumpsite, slaughterhouse) (Table 1).

The result revealed that the pH value in Calabar Municipality both in the dumpsite and slaughterhouse areas was the lowest; meaning the boreholes in those areas had a strong acidic content. However, while comparing the pH in the borehole water samples from the different LGAs, excluding the source of collection, it was observed that the pH value from Yala and Ogoja was the highest, followed by Akamkpa and Ikom, also followed by the pH value from Yakurr while Calabar Municipality had the lowest pH value (Table 2). This result implies that the borehole

water samples from the pollution prone areas were acidic.

Electrical conductivity: The borehole located at Ikom (control), Ogoja and Yakurr (control, dumpsite) and Yala (control, slaughter) had significantly high level of conductivity than the mean values obtained from Akamkpa (control), Cal. M (control), Ikom (dumpsite, slaughterhouse), Yakurr (slaughterhouse) and Yala (dumpsite) with no significant difference (P>0.05). This was followed by the conductivity value obtained from Calabar Municipality (dumpsite), Akamkpa (dumpsite), Ogoja (slaughterhouse) while, Cal. Slaughterhouse had lower conductivity level (Table 1). Table 2 shows that the boreholes from Yakurr and Yala had the highest conductivity level, followed by Ikom. The conductivity level from Akamkpa and Calabar Municipality was the lowest. This result implies that the conductivity levels in the borehole water samples from the different locations were lower than the WHO standard for drinking water and that the ionic concentration of the water was low.

Total Dissolved Solid (TDS): The result as presented on Table 1 indicates that the TDS in borehole located at Ogoja (dumpsite), had the highest TDS value than other boreholes. This was followed by the TDS values from Ikom and Yakurr (dumpsite), Yala (control) with no significant difference (P>0.05) in mean. While, the TDS value from Akamkpa and Calabar municipal (control, dumpsite, slaughterhouse), Ikom, Yakurr and Ogoja (control, slaughterhouse), Yala (dumpsite and slaughterhouse) was the lowest with no significant variation in mean. However, Table 2 show that the TDS value from borehole water samples was the highest, followed by the TDS in boreholes from Ikom and Yakurr that shows no significant differences (P > 0.05) in mean values, while Akamkpa and Calabar Municipality had the lowest TDS in their borehole water. This result based on the WHO standard for drinking water implies that the level of TDS was below the WHO recommended standard.

Turbidity: The result obtained show that water samples from Ikom (dumpsite) had the highest turbidity level, followed by the turbidity level in borehole water samples from Ikom (slaughterhouse), Ogoja (dumpsite), and Yala (control) with no significant difference (P>0.05). This was also followed by the turbidity level in borehole water samples in Akamkpa, Ikom and Ogoja (control) with no significant difference

Location	Source	рH	Conductivity	TDS	Turbidity	AL	Calcium	Phosphate	Floride	Nitrate
Akamkpa	Control	$6.70^{\rm b}$ ±0.12	$203.33^{b} \pm 7.17$	64.33° ±4.26	$7.33c_{\pm}0.38$	0.09° ±0.01	$14.43b \pm 1.35$	5.90^{h} ±0.78	0.26° ±0.04	$5.04c_{\pm}0.20$
	Dumpsite	$6.23b + 0.20$	139.67 ^c ±7.13	71.0° ±4.36	$3.31^{f} \pm 0.44$	$0.46^a \pm 0.02$	18.57 ^a ±080	$24.49b + 2.73$	$0.62^a \pm 0.09$	$17.73a_{\pm}0.90$
	Slaughterhouse	5.60° ±0.13	$39.0^{\rm d}$ ±14.64	14.0° ±4.58	5.28^{d} ±0.24	$0.081c_{\pm}0.04$	$12.5^{\rm b}$ ±1.00	9.139 ± 0.61	$0.35c_{\pm}0.05$	$7.35c + 1.59$
Cal. M	Control	$6.23b + 0.12$	241.0^b ±4.93	85.67 ^c ±3.84	5.70^{d} ±0.07	$0.08c_{\pm}0.02$	$20.93^a \pm 0.81$	8.029 ± 1.34	$0.45^{\rm b}$ ±0.03	$7.03c_{\pm}0.07$
	Dumpsite	4.26° ±0.09	117.0° ±13.05	57.67° ±6.39	1.58^h ±0.07	$0.40^{\rm b}$ ±0.09	$20.73^a \pm 0.82$	$12.18^{f} \pm 3.34$	$0.58^a \pm 0.02$	$12.96^{\rm b}$ ±2.43
	Slaughterhouse	4.83^{d} ±0.18	31.33^{d} ±6.76	16.00° ±3.61	1.93^h ±0.23	0.39^b ±0.08	16.35^{b} ±0.10	20.16 ^c ±4.64	$0.68^a \pm 0.09$	$14.04b \pm 0.77$
Ikom	Control	$6.50^{\rm b}$ ±0.12	603.67 ^a ±51.33	157.0 ^c ±12.74	7.10° ±0.12	$0.063c_{\pm}0.01$	$11.67^b \pm 0.18$	9.069 ± 0.58	$0.21c_{\pm}0.06$	3.97° ±0.44
	Dumpsite	$6.03b + 0.09$	286.67 ^b ±35.67	$225.0^{\rm b}$ ±13.61	$8.94^a \pm 1.06$	0.16° ±0.03	$18.07^a \pm 1.61$	$23.43b \pm 0.94$	$0.54^a \pm 0.01$	$5.85c_{\pm}0.31$
	Slaughterhouse	5.50° ±0.02	283.33 ^b ±29.87	$113.0°+47.70$	8.15^{b} ±1.19	0.16° ±0.05	$16.37^b \pm 0.67$	15.85° ±5.47	$0.36c_{\pm}0.10$	$6.08c_{\pm}0.07$
Ogoja	Control	6.70^b ±0.12	501.33 ^a ±44.82	161.67 ^c ±3.84	$7.28c_{\pm}0.14$	0.02° ±0.002	$13.57^b \pm 0.41$	$4.59h \pm 0.69$	0.22^c ±0.01	$1.34c + 0.28$
	Dumpsite	6.43^b ±0.20	486.67 ^a ±29.81	$336.0^a \pm 73.76$	8.20^{b} ±0.09	$0.08c_{\pm}0.01$	$15.1b \pm 1.66$	$27.73a_{\pm}11.42$	$0.55^a \pm 0.07$	7.37° ±2.87
	Slaughterhouse	$6.47^b \pm 0.20$	144.33°±7.88	69.00° ±2.08	3.30^{f} ±0.7	$0.07c_{\pm}0.02$	$21.17^a \pm 1.39$	18.17^{d} ±0.43	$0.74^a \pm 0.04$	$2.78c_{\pm}0.62$
Yakurr	Control	$5.67c_{\pm}0.23$	420.67 ^a ±41.95	152.67 ^c ±20.03	5.45^d ±0.25	$0.07c_{\pm}0.03$	$9.97^b \pm 0.27$	8.309 ± 0.03	0.10° ±0.00	$5.24c_{\pm}0.44$
	Dumpsite	$5.27c_{\pm}0.23$	578.67 ^a ±84.23	272.67 ^b ±10.17	2.799 ± 0.23	0.12° ±0.02	$19.18^a \pm 0.48$	18.17^{d} ±0.78	0.19° ±0.01	$17.31a_{\pm}2.89$
	Slaughterhouse	$5.13c_{\pm}0.09$	217.00 ^b ±45.79	68.33° ±0.88	2.02^h ±0.16	$0.06c_{\pm}0.01$	$12.80^{\rm b}$ ±0.91	$13.70^{f} \pm 2.30$	$0.14c_{\pm}0.03$	$7.64c_{\pm}0.33$
Yala	Control	$7.00^a \pm 0.15$	541.0 ^a ±10.69	$223.67^b \pm 11.70$	$7.97^b \pm 0.49$	0.03° ±0.001	$11.13b \pm 0.85$	8.639 ± 0.26	0.20° ±0.01	$3.11^c \pm 0.17$
	Dumpsite	$6.37^b \pm 0.60$	$232.0^b \pm 5.51$	105.33 ^c ±10.41	5.26^{d} ±0.31	0.09° ±0.02	$12.73b \pm 0.69$	20.89 ^c ±2.62	$0.61^a \pm 0.03$	$12.27^{\rm b}$ ±0.32
	Slaughterhouse	$6.30b + 0.12$	469.33 ^a ±60.76	139.0 ^c ±44.19	4.80° ±0.15	$0.05c_{\pm}0.01$	20.10^a ±1.00	15.50° ±1.26	0.29° ±0.04	2.98° ±1.16
LSD		0.23	56.80	46.86	0.43	0.04	1.26	1.64	0.07	1.85
WHO		$6.5 - 8.5$	500	250		0.02	0.1	5.0		
NIS		$6.5 - 8.5$	1000	500		0.2	50		1.0	15

Table 1. Physicochemical properties of underground water in polluted soil prone areas

Table 2. Physicochemical Properties of ground water collected from different Local Government Area in CRS

Mean with the same superscript along the vertical arrays indicates no significant difference (P>0.05)

Table 3. Heavy metal content of underground water in polluted soil prone areas

Mean with the same superscript along the vertical arrays indicates no significant difference (P>0.05)

Table 4. Heavy metal content of ground water collected from different Location Government Area in CRS

Mean with the same superscript along the vertical arrays indicates no significant difference (P>0.05)

(P>0.05) in the mean but significantly higher than the turbidity level Akamkpa (slaughterhouse), Calabar Municipality and Yakurr (control), and Yala (dumpsite) while the lowest turbidity level was obtained from borehole water samples from Calabar Municipality (dumpsite, slaughterhouse), and Yakurr (slaughterhouse) with no significant variation in the mean values (Table 1). It was observed that the turbidity of borehole water in Ogoja and Yala was the highest, followed by the values obtained from Akamkpa, also followed by the value obtained from Yakurr while the lowest turbidity value was obtained from the borehole water situated in Ikom (Table 2).

Aluminum: The result show that high Al was detected in Akamkpa (dumpsite), followed by the Al content obtained from Calabar Municipality (dumpsite, slaughterhouse) with no significant difference (P>0.05) in mean, but significantly higher than the mean Al content found in other locations and sources (Table 1). However, the Al content in Akamkpa, Calabar Municipality was higher than the Al content Ikom, while Al content in the borehole water from Ogoja, Yakurr and Yala was observed to be the lowest. This result implies that Akamkpa and Calabar Municipality had the highest Al content in their boreholes.

Ammonia and biochemical oxygen demand: The result as presented on Figs. 1, 2 and 3 signified that the ammonia, BOD level, and temperature in the borehole water samples from the different locations and sources showed no significant difference (P>0.05) in the mean values obtained.

Calcium: The result as presented on Table 1 show that Akamkpa and Ikom (dumpsite), Calabar Municipality (control, dumpsite), Ogoja and Yala (slaughterhouse), had significantly high (P>0.05) levels of calcium in the borehole water, higher than the calcium level in other borehole water samples. Table 2 show that the calcium levels in the borehole water from Calabar Municipality was the highest, followed by the Ca level in Ogoja boreholes, followed by the Ca levels in Akamkpa and Ikom borehole with no significant difference (P>0.05) in mean while the Ca level in Yakurr was the lowest.

Phosphate: It was observed from the result that the phosphate in boreholes from Ogoja (dumpsite) was the highest, significantly higher $(P<0.05)$ than the PO4²⁻ in Akamkpa and Ikom (dumpsite) with no significant difference in mean

but significantly higher (P<0.05) than the $PO4²$ in Calabar Municipality (slaughterhouse) and Yala (dumpsite) boreholes. The lowest PO42- value was obtained in Akamkpa and Ogoia (control) boreholes. Table 2 show that the PO4²⁻ content in Ogoja boreholes was the highest, followed by the PO42+ content in Ikom boreholes while Akamkpa and Calabar Municipality boreholes was the lowest.

Fluoride: The availability of fluoride in borehole water from Akamkpa (dumpsite), Calabar Municipality (dumpsite, slaughterhouse), Ikom (dumpsite), Ogoja (dumpsite, slaughterhouse) and Yala (dumpsite) was the highest, with no significant difference (P>0.05) in the mean values obtained. This was followed by the fluoride content in boreholes water from Calabar Municipality (control), significantly higher than the fluoride content in other boreholes water samples, which equally showed no significant difference (P>0.05) in mean Table 1. The comparison between the fluoride levels among the different borehole locations show that Akamkpa, Calabar Municipality Ikom, Ogoja, Yala had the highest fluoride content, while, Yakurr had the lowest (Table 2).

Nitrate: The result as presented on Table 1 show that Akamkpa and Yakurr (dumpsites) had the highest nitrate levels in their boreholes. This was followed by the nitrate levels in Calabar Municipality (dumpsite, slaughterhouse) and Yala (dumpsite) with no significant difference (P>0.05) in the mean values obtained but significantly higher than the nitrate content in the boreholes situated at Akamkpa, Yala and Yakurr (control and slaughterhouse), Calabar Municipality (control), Ikom and Ogoja (control, dumpsite, slaughterhouse) with no significant difference (P>0.05) in the mean values. It was also observed that the nitrate level in Calabar Municipality borehole was the highest, followed by the nitrate level in borehole water in Akamkpa and Yakurr that show no difference (P>0.05) in means while the nitrate level in Ogoja borehole had the lowest nitrate level (Table 2).

3.2 Heavy Metal Content in Groundwater

Iron (Fe): The result as presented on Table 3 show that the iron level in Calabar Municipality (dumpsite) borehole was the highest, followed by Akamkpa and Yala (dumpsite) boreholes with no significant difference (P>0.05) in the mean values. This was followed by the iron content in other borehole water samples in different locations and sources during the research. Table 4 show that the iron content in Akamkpa borehole was the highest, followed by the iron content in borehole water from Calabar Municipality and Yala while, Ikom, Ogoja and Yakurr boreholes had the lowest iron content with no significant difference (P>0.05) in mean.

Zinc (Zn) content: It was observed from Table 3 that the zinc level in Ogoja (slaughterhouse) ground water was significantly low. While borehole water samples from other sources and locations were significantly high in zinc. Table 4 revealed that the zinc in Akamkpa and Ogoja water samples was significantly higher (P<0.05) than the zinc level in Calabar Municipality and Yala boreholes water samples, this was followed by the zinc level in Ikom borehole while, Yakurr had the lowest zinc.

Chromium (Cr) content: The chromium level in Ogoja (slaughterhouse) was significantly higher (P<0.05) than the Cr level in borehole water samples from other locations and sources that appears to be significantly low with no variation in mean (Table 3). The result as presented on Table 4 show that the chromium content in Ikom and Yakurr boreholes was the highest with no significant difference (P>0.05) in the mean values. This was followed by the chromium content in borehole water from Akamkpa, Ogoja, Yala with no variation in means. While the chromium content in Calabar Municipality was the lowest.

Copper and manganese: The results as presented on Tables 3 and 4 show that the copper and manganese content in ground water samples from the different locations and sources were not significantly different (P>0.05).

Fig. 1. Ammonia content in the borehole water samples

Fig. 2. Biochemical oxygen demand in the borehole water

Fig. 3. Temperature in the borehole water

4. DISCUSSION

4.1 Effect of Pollutants on the Physicochemical Properties of Groundwater

The temperature values were within the range for a tropical aquatic system (<40°C). The pH quantifies the level of acidity and alkalinity of particular substance or solution. The acidic pH values recorded from most of the dumpsites falls outside the recommended range suitable for drinking. This aligns with Garg [4], who reported pH deviation from the neutral range due to the discharge of acidic industrial effluents. The observed acidity maybe as a result of humic acid formed from decaying organic matter from leachate. Ground water pH has also been known to influence the dissolution of minerals in a groundwater system as well as affects the quality for various purposes. This is in line with reports from Rim-Rukeh [19] and Cleary [20], that decaying organic matter contributes to humic acid formation and leaching into groundwater with a resultant increased acidity or alkalinity of the groundwater.

The present study revealed that fluoride which is distributed in the lithosphere and hydrosphere varied significantly among the dumpsites and abattoirs in Yakurr and Calabar Municipality. The concentration of fluoride in the water samples studied falls short of the World Health Organization [21] guideline value for fluoride concentration. This could be attributed to high amount of total dissolved solids in the groundwater in the study area with high volume of cations which combine with fluoride to form complexes, thus making fluoride unavailable in free form. This agrees with the position of Odukoya [22].

Biochemical oxygen demand (BOD) of dissolved oxygen concentration in natural waters depends on the physical, chemical and biochemical activities in the water body. BOD values obtained from the polluted sites across the study area were lower than the [23] water quality standards but the values were higher than all the control. This could be attributed to the high levels of nutrients, organic loads and total solids content of effluents from these dumpsites and abattoirs. BOD is very crucial for the survival of aquatic organisms [24]. The depletion of BOD at this discharge points (DP) may also be attributed to the enormous amount of organic loads which required high levels of oxygen for chemical oxidation, decomposition of nutrients or break

down thereby depleting available oxygen required for respiration. Similar findings have been reported from abattoir effluent by Chukwu [25], Arimoro [26].

The electrical conductivity was recorded in high levels at very few discharge points from the study area. The observed values could be attributed to the high levels of conducting elements such as aluminum, fluoride and phosphate. Fakayode [27], reported also that conducting elements contributed to the high electrical conductivity in a studied dumpsite.

Phosphates can get into water through anthropogenic sources, animal waste, phosphorus rich bedrock, laundry, cleaning, industrial effluents and fertilizer runoff. The present study showed the presence of high levels of phosphates in the dumpsites and abattoirs. The high level of phosphate in the water samples could be due to the leaching of fertilizer residues from agricultural farm lands along the pathways and water bodies, as well as soap and detergent used for washing by slaughterhouse people. This is in line with Fakayode [27], Kumar [28] who recorded other sources of phosphate to include detergents used by the abattoir workers to wash roasted slaughtered animals, and laundry activities of surrounding residents which run-off into the river.

4.2 Effect of Pollutants on Heavy Metals Contamination of Ground Water

The relatively high concentrations of heavy metals may be attributed to the salt contaminating nature in some of these locations like Akamkpa with limestone which easily dissolves in water affects ground water. The concentration of the studied heavy metals, iron, zinc, chromium, manganese and aluminum in ground water in all six locations are not above the typical international standards limits for drinking water. Kana [13] corroborates this in an investigation focused on the quality of groundwater in Karu, Central Nigeria, which revealed that the concentrations of heavy metals such as cadmium (Cd), chromium (Cr), copper (Cu), iron (Fe), manganese (Mn), nickel (Ni), lead (Pb), and zinc (Zn) in the groundwater samples were generally within the permissible limits set by the WHO. In contrast, [14]**,** found that the concentrations of heavy metals like arsenic (As), cadmium (Cd), lead (Pb), and mercury (Hg) in some water samples exceeded the WHO guidelines, indicating potential health risks.

Iron remains the most abundant element by weight in the earth's crust and the second most abundant metal in the earth crust. The iron concentrations estimated in the groundwater sample collected from the dumpsites and abattoirs are more or less within the range of 0.3 mg/l with exceptions from Akamkpa, Calabar Municipality and Yala dumpsites, which showed iron contents of relatively higher concentrations above the NIS regulation. This finding is in agreement with the reports of World Health Organization [23].

5. CONCLUSION

Unhygienic water is detrimental to human health and affects the physiological features of humans. The result of this investigation shows clearly that the physical, chemical, and heavy metal of the water in the different local government areas examined were high and could be injurious to
human health. Therefore, Abattoirs and human health. Therefore, Abattoirs and dumpsites should be sited in distance areas away from residential areas.

DISCLAIMER (ARTIFICIAL INTELLIGENCE)

Authors hereby declare that NO generative AI technologies such as Large Language Models (ChatGPT, COPILOT, etc) and text-to-image generators have been used during writing or editing of manuscripts.

ACKNOWLEDGEMENTS

A brief acknowledgement section may be given after the conclusion section just before the references. The acknowledgments of people who provided assistance in manuscript preparation, funding for research, etc. should be listed in this section. All sources of funding should be declared as an acknowledgement. Authors should declare the role of funding agency, if any, in the study design, collection, analysis and interpretation of data; in the writing of the manuscript. If the study sponsors had no such involvement, the authors should so state.

COMPETING INTERESTS

Authors have declared that no competing interests exist.

REFERENCES

1. Kumar A, Singh R. Recent advances in water quality assessment: A review.

Environ Sci Pollut Res. 2022;29(12): 17845-60.

- 2. Zhang Y, et al. Heavy metal contamination in groundwater: Sources, effects, and remediation strategies. Water Res. 2023;220:118-30.
- 3. Ogunfowokan AO, Ojo JA. Impact of urbanization on groundwater quality: A case study. J Environ Manage. 2023;320:115-25.
- 4. Garg A, Kumar P, Gupta AK. The influence of acidic industrial effluents on water pH and its implications for aquatic ecosystems. J Environ Manag. 2021; 295:113128.
- 5. Rakib MA, Sasaki J, Matsuda H, Quraishi SB, Mahmud MJ, Bodrud-Doza M, et al. Groundwater salinization and associated co-contamination risk increase severe drinking water vulnerabilities in the southwestern coast of Bangladesh. Chemosphere. 2020; 246:125646.
- 6. Gapparov A, Isakova M. Study on the characteristics of water resources through electrical conductivity: A case study of Uzbekistan. IOP Conf Ser Earth Environ Sci. 2023; 1142(1):012057.
- 7. Chris-Otubor GO, Olorunfemi P. Evaluation of some industrial effluents in Jos metropolis, Plateau State, Nigeria. Afr J Environ Sci Technol. 2015; 9(6):566-72.
- 8. Sanad H, Mouhir L, Zouahri A, Moussadek R, El Azhari H, Yachou H, et al. Assessment of groundwater quality using the pollution index of groundwater (PIG), nitrate pollution index (NPI), water quality index (WQI), multivariate statistical analysis (MSA), and GIS approaches: A case study of the Mnasra region, Gharb Plain, Morocco. Water. 2024; 16(9):1263.
- 9. Abdullahi AB, Siregar AR, Pakiding W, Mahyuddin. The analysis of BOD (biological oxygen demand) and COD (chemical oxygen demand) contents in the water of around laying chicken farm. Earth Environ Sci. 2021; 788:012155.
- 10. Fardiaz S. Polusi air dan udara. Yogyakarta: Kanisius; 2003.
- 11. Aniyikaiye TE, Oluseyi T, Odiyo JO, Edokpayi JN. Physico-chemical analysis of wastewater discharge from selected paint industries in Lagos, Nigeria. Int J Environ Res Public Health. 2019; 16(7):1235.
- 12. Omonona AO, Solotan TV, Adetuga AT. Heavy metals contamination in water, soil and plant samples of Okomu National

Park, Edo State, Nigeria. Afr J Biomed Res. 2020; 23(1):29-34.

- 13. Kana AA. Heavy metal assessment of groundwater quality in part of Karu, Central Nigeria. Water Pract Technol. 2022; 17(9): 1802-17.
- 14. Mawari G, Kumar N, Sarkar S, Frank AL, Daga MK, Singh MM, et al. Human health risk assessment due to heavy metals in ground and surface water and association of diseases with drinking water sources: A study from Maharashtra, India. Environ Health Insights. 2022; 16: 11786302221146020.
- 15. Singh A, Sharma A, Verma RK, Chopade RL, Pandit P, Nagar V, et al. Heavy metal contamination of water and their toxic effect on living organisms. Intech Open; 2022.

DOI: 10.5772/intechopen.105075.

- 16. Iyakndue ML, Brooks AA, Unimke AA, Agbo BE. Effects of palm oil mill effluent on soil microflora and fertility in Calabar– Nigeria. Asian J Biol. 2017;2(3):1-11.
- 17. Okwute LO, Isu NR. The environmental impact of palm oil mill effluent (POME) on some physicochemical parameters and total aerobic bio-load of soil at a dump site in Anyigbe, Kogi State, Nigeria. Afr J Agric Res. 2007;2(12):656-62.
- 18. Ogunmodede OT, Ajayi OO, Amoo IA, Adewole E. Characterization of dumpsite: Case study of Ado-Ekiti and Ijero Ekiti, Nigeria. J Environ Sci Toxic Food Technol. 2013; 3(6):43-50.
- 19. Rim-Rukeh A, Ikhifa OG, Okokoya AP. Effects of agricultural activities on the

water quality of Orogodo River, Agbor Nigeria. J Appl Sci Res. 2006; 2: 256-9.

- 20. Cleary DF, Devantier. Industrial effluent. In: Encyclopedia of Environmental Health. Second Edition; 2019.
- 21. World Health Organization. International standards for drinking water. 3rd ed. Geneva. 2006;346-85.
- 22. Odukoya AM, Abimbola AF. Contamination assessment of surface and groundwater within and around two dumpsites. Int J Environ Sci Technol. 2010; 2(2):367- 76.
- 23. World Health Organization. Guidelines for drinking-water quality. 3rd ed. Vol. 1. Geneva, Switzerland: World Health Organization; 2003.
- 24. Yakub AS, Ugwumba AAA. A study on the macroinvertebrate fauna of lower Ogun River at Ishasi, Ogun state, south-west Nigeria. Zoologist. 2009; 7:65-74.
- 25. Chukwu O. Analysis of groundwater pollution from abattoir waste in Minna, Nigeria. Res J Dairy Sci. 2008; 2:74-7.
- 26. Arimoro FO, Chukwudi MA, Ogheneghalome O. Effect of industrial waste water on the physical and chemical characteristics of a tropical coastal river. Res J Environ Sci. 2007; 2:209-20.
- 27. Fakayode SO. Impact assessment of industrial effluent on water quality of the receiving Alaro stream in Ibadan, Nigeria. J Ajeam-Ragee. 2005; 10:1-13.
- 28. Kumar M, Puri A. A review of permissible limits of drinking water. Indian J Occup Environ Med. 2012; 16(1):40-4.

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of the publisher and/or the editor(s). This publisher and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.

© Copyright (2024): Author(s). The licensee is the journal publisher. This is an Open Access article distributed under the terms of the Creative Commons Attribution License (http://creativecommons.org/licenses/by/4.0), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

> *Peer-review history: The peer review history for this paper can be accessed here: <https://www.sdiarticle5.com/review-history/122377>*